

MolokDomino containers are made to last for decades of intense use. However, maintenance and cleaning extend the life time of the containers. Regular maintenance also guarantees that the recycling station stays clean and safe for all users.

Container is 2800 mm high, from which 1500 mm is situated underground. Container consists of well body, lifting bag or lifting container and a lid.

Framing: The unpainted wooden framing parts are processed with tree oil once a year. Other framing materials can be washed when necessary.

Lid: Lid is washed once a year or when necessary, i.e. with Würth Pinline Power wash. Waxing the lid in every two years after wash eases the cleaning, i.e. Autoglym Supersheen wax can be used.

The entire container can be washed when necessary.

Lock: If the container is equipped with lock, the lock should be oiled at least twice a year.

During emptying of the container all possible damages such as cuts, cracks and tears should be checked from:

- the lid
- possible quick system
- lifting bag - check especially: closing rope, rope lock and lifting loops



SWL limits for lifting bags		
5 m ³	1/1	1250 kg
3 m ³	2/3	1250 kg
2,4 m ³	1/2	1250 kg
1,5 m ³	1/3	1000 kg

Molok Ltd. warrants that the Molok® product is free from defects in material and workmanship under normal use. Warranty period from the date of delivery:

- lifting bags and lids 2 years
- body wells 10 years
- lifting container 10 years;
- warranty doesn't cover mechanical parts
- other parts 1 year (except Bioska bags for organic waste)